

ELECTRIC BASEBOARD

Enjoy the simple warmth of reliable, quiet convection heat. These high-quality baseboards are designed for easy installation and exceptional durability, providing reliable performance to warm any space for years to come.

TBTK-SP / DP
- Built-in
Thermostat Kit



BENEFITS

- Practical design is built to last and ideal for replacement and retrofit applications
- Easy installation with pre-punched markings at 1-inch intervals
- Universal wiring available at either end
- Proven construction helps maximize surface area and funnel heated air
- Place under a window for best results
- Silent operation with no moving parts

APPLICATIONS

All Residential Applications | Commercial Offices | Lobbies



SPECIFICATIONS

Voltage	240V/208V, 208V
Wattage	Sizes ranging from 300W to 2500W
Color	White
Finish	Powder coating resists fading and abrasion
Construction	Case, cover, and deflector are made of 24 gauge steel with 20 gauge junction boxes containing a grounding screw
Heating Element	Element is totally enclosed, providing superior life expectancy and resistance to rust
Warranty	10-year element warranty 1-year warranty on complete unit

BUILT-IN THERMOSTATS

Cat. No.	Description	Volts	Amps
TBTK-SP	Single pole built-in thermostat kit	120 / 208 / 240	22
TBTK-DP	Double pole built-in thermostat kit	120 / 208 / 240	22



TBTK-SP



TBTK-DP

ORDERING GUIDE

Cat. No.	Watts	Volts	BTU	Length (mm/in)	Weight (kg/lbs.)
TB2403W21	300	208	1023	609 / 24	2.68 / 5.9
TB3005W21	500	208	1710	762 / 30	2.72 / 6
TB3005W31	500 / 375	240 / 208	1710 / 1280	762 / 30	2.72 / 6
TB3607W21	750	208	2560	914 / 36	3.18 / 7
TB3607W31	750 / 563	240 / 208	2560 / 1925	914 / 36	3.18 / 7
TB4810W21	1000	208	3415	1219 / 48	4.08 / 9
TB4810W31	1000 / 750	240 / 208	3415 / 2560	1219 / 48	4.08 / 9
TB6012W21	1250	208	4265	1524 / 60	4.54 / 10
TB6012W31	1250 / 937	240 / 208	4265 / 3200	1524 / 60	4.54 / 10
TB6615W21	1500	208	5120	1676 / 66	5.44 / 12
TB6615W31	1500 / 1125	240 / 208	5120 / 3840	1676 / 66	5.44 / 12
TB8420W21	2000	208	6825	2134 / 84	7.26 / 16
TB8420W31	2000 / 1500	240 / 208	6825 / 5120	2134 / 84	7.26 / 16
TB10225W21	2500	208	8530	2591 / 102	8.16 / 18
TB10225W31	2500 / 1875	240 / 208	8530 / 6400	2591 / 102	8.16 / 18

DIMENSIONS

